







PRODUCT	CONTRACTOR	WAI EK HAKUNESS Oft	ium		APPLICATION ight	ium	Ŋ	METAL	sno	Non-ferrous	APPLICATIONS	
任 METAL REMOVAL FLUIDS	5	Soft	Medium	Hard	APP	Medium	Heavy	M	rerrous	Non	AP	
MEIAL KEMUVAL FLUIDS								<u> </u>				
QUAKERCOOL® 2766	Synthetic											Light to medium duty machining and grinding, and some light machining on aluminum alloys
QUAKERCOOL® 2776	Synthetic											Heavy duty machining and grinding of cast iron and ferrous metals
QUAKERCOOL® 3511	Semi-Synthetic											Machining and grinding of cast iron and some steel alloys
QUAKERCOOL® 3750	Semi-Synthetic											Machining and grinding applications, including difficult cast iron and steel
QUAKERCOOL® 7102	Semi-Synthetic											General purpose machining and grinding of ferrous metals and some light duty aluminum operations
QUAKERCOOL® 7020 CG	Semi-Synthetic											Machining, grinding and honing of CGI alloys
QUAKERCOOL® 7105	Semi-Synthetic		•	•			•			•		General purpose machining and grinding of cast iron, ferrous and some non-ferrous metals; chlorinated metalworking technology
QUAKERAL® 481	Micro-Emulsion											Machining of aluminum, cast iron and steel
QUAKERAL® 388 PE	Micro-Emulsion											Heavy duty machining and grinding applications
QUAKERCUT® 004 PE	Straight Oil	N/A	N/A	N/A								Honing, lapping and grinding operations
QUAKERCUT® 010 ES	Straight Oil	N/A	N/A	N/A								Medium to heavy-duty machining, tapping, gun drilling and plated CBN grinding
CORROSION PREVENTIVES												
FERROCOTE® 5856 BFT1	Oil/Solvent	N/A	N/A	N/A								Long term corrossion protection -1 year+
FERROCOTE® 118 EC	Emulsifiable				_							Medium term corrosion protection - 3-6 months
FERROCOTE® 614 AAM	Synthetic	•	•	•	•					•		Short term corrosion protection - 30 days
CLEANERS												
QUAKERCLEAN® 624 MPC	Synthetic		•		•							Synthetic, semi-synthetic, emulsifiable coolant removal
QUAKERCLEAN® 520 TOR	Synthetic											Quench oil, honing oil, straight oil removal
QUAKERCLEAN® 628 TK	Synthetic	•	•									Corrosion preventive removal
QUAKERCLEAN® 613 DPD	Synthetic											Sump cleaner
QUAKER FORMULATM FX THUNDER	Synthetic	•	•									Maintenance cleaner, tire marks removal
HYDRAULIC FLUIDS												
QUINTOLUBRIC® 888	HFD-U: polyol ester		Excellent lubrication, excellent shear stability, fire resistant, simple waste treatment									Hydraulics in hazardous high temperature or fire prone areas
QUINTOLUBRIC® 702-46 RD	HFC: water glycol		Maximum fire resistance, enhanced job site safety, reduced downtime, lower maintenance costs									Hydraulics in hazardous high temperature or fire prone areas